



GROOVE IN1 | 7,5 W | 230 V | 1125 Lm | CRI > 90

IP20 **A++**



TYPE

GRV.IN1



Finishing

White

Optic

- 8° **01**
- 13° **02**
- 30° **03**
- 47° **04**
- 66° **05**
- Elliptic **06**

Color

- 2800 K** .EW
- 3200 K** .WW
- 4200 K .NW
- 5500 K .CW
- Tunable** .TW

Accessories

Driver remoto
Remote Driver



Pag. 454

Kit fissaggio incluso
Fixing kit included

More features

Emergency 1-3 H

.33

DALI 1-10 V, switch DIM

.44

CROMALINE

Pag. 014



GROOVE IN2 | 15 W | 230 V | 2250 Lm | CRI > 90

IP20 **A++**



TYPE

GRV.IN2



Finishing

White

Optic

- 8° **01**
- 13° **02**
- 30° **03**
- 47° **04**
- 66° **05**
- Elliptic **06**

Color

- 2800 K** .EW
- 3200 K** .WW
- 4200 K .NW
- 5500 K .CW
- Tunable** .TW

Accessories

Driver remoto
Remote Driver



Pag. 454

Kit fissaggio incluso
Fixing kit included

More features

Emergency 1-3 H

.33

DALI 1-10 V, switch DIM

.44

CROMALINE

Pag. 014

GRV.IN2

GRV.IN1

FINISHING

CROMALINE

