

HANG 1

FINISHING

---.14

---.18



CROMALINE



HANG 1.1 | 21,6 W | 24 V | 3240 Lm | CRI > 90


IP40 A++




TYPE

70101

Ø17



each lenght from  
200 mm to 1000 mm



Cover

Transp	.1
Opal	.2

Finishing

Anod. Alum	.14
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW

Accessories

D.01.100

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto  
Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 1.2 | 32,4 W | 24 V | 4860 Lm | CRI > 90


IP40 A++




TYPE

70102

Ø17



each lenght from  
1001 mm to 1500 mm



Cover

Transp	.1
Opal	.2

Finishing

Anod. Alum	.14
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW

Accessories

D.01.150

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto  
Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 1.3 | 43,2 W | 24 V | 6480 Lm | CRI > 90

IP40 A++



TYPE

70103

Ø17



each lenght from  
1501 mm to 2000 mm



Cover

Transp	.1
Opal	.2

Finishing

Anod. Alum	.14
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW

Accessories

D.01.200

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto  
Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014