

CODE COMPOSITION: type + cover + finishing + color ( + more features ) + xxxx mm

Tutti i parametri tecnici si riferiscono alla lampada nella sua lunghezza massima  
All technical features refer to the lighting fixture in its maximum length

HANG 60.1 | 12,5 W | 24 V | 1250 Lm | CRI > 90

IP40 A++




TYPE

**76001**

Ø10.5

each lenght from 200 mm to 1000 mm

Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2	Anod. Alum .14	3000 K .WW
	Anod. Black .18	3500 K .LW
		4000 K .NW



Accessories

**D.60.100**

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 60.2 | 19 W | 24 V | 1920 Lm | CRI > 90

IP40 A++




TYPE

**76002**

Ø10.5

each lenght from 1001 mm to 1500 mm

Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2	Anod. Alum .14	3000 K .WW
	Anod. Black .18	3500 K .LW
		4000 K .NW



Accessories

**D.60.150**

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 60.3 | 25 W | 24 V | 2500 Lm | CRI > 90

IP40 A++



TYPE

**76003**

Ø10.5

each lenght from 1501 mm to 2000 mm

Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2	Anod. Alum .14	3000 K .WW
	Anod. Black .18	3500 K .LW
		4000 K .NW



Accessories

**D.60.200**

Rosone con driver integrato  
Base for ceiling driver included



Driver remoto Remote Driver  
Pag. 454



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014