

HANG 76

FINISHING

---.11

---.18




CROMALINE

CODE COMPOSITION: type + cover + finishing + color (+ more features) + xxxx mm

Tutti i parametri tecnici si riferiscono alla lampada nella sua lunghezza massima
All technical features refer to the lighting fixture in its maximum length

HANG 76.1 | 21,6 W | 230 V | 3240 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Satin .1	White .11	2700 K .EW
Opal .2	Anod. Black .18	3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW




Driver integrato
Integrated driver

More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 76.2 | 32,4 W | 230 V | 4860 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Satin .1	White .11	2700 K .EW
Opal .2	Anod. Black .18	3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW




Driver integrato
Integrated driver

More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 76.3 | 43,2 W | 230 V | 6480 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Satin .1	White .11	2700 K .EW
Opal .2	Anod. Black .18	3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW



Driver integrato
Integrated driver

More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014


HANG 76.4 | 21,6 W DOWN / 40 W UP | 230 V | 3240 Lm DOWN / 5200 Lm UP | CRI > 90

IP40 A++



TYPE

77604



each lenght from
400 mm to 1000 mm

Cover

Satin	.1
Opal	.2

Finishing

White	.11
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable CASAMBI	.TW

Driver integrato
Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014


HANG 76.5 | 32,4 W DOWN / 60 W UP | 230 V | 4860 Lm DOWN / 7800 Lm UP | CRI > 90

IP40 A++



TYPE

77605



each lenght from
1001 mm to 1500 mm

Cover

Satin	.1
Opal	.2

Finishing

White	.11
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable CASAMBI	.TW

Driver integrato
Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014


HANG 76.6 | 43,2 W DOWN / 80 W UP | 230 V | 6480 Lm DOWN / 10400 Lm UP | CRI > 90

IP40 A++



TYPE

77606



each lenght from
1501 mm to 2000 mm

Cover

Satin	.1
Opal	.2

Finishing

White	.11
Anod. Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable CASAMBI	.TW

Driver integrato
Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

