



TYPE	Cover	Finishing	Color
78101	Satin .1	White .11	2700 K .EW
	Opal .2	Anod. Alum .14	3000 K .WW
		Black .18	3500 K .LW
			4000 K .NW
			6500 K .CW
			Tunable CASAMBI .TW



Driver integrato
Integrated driver 

Emergency 1-3 H **.33** DALI 1-10 V, switch DIM **.44**  Pag. 014

HANG 81.2 | 60 W | **230 V** | 7800 Lm | CRI > 90



TYPE	Cover	Finishing	Color
78102	 .1	 .11	 .EW
	 .2	 .14	 .WW
		 .18	 .LW
			 .NW
			 .CW
			 .TW



Driver integrato
Integrated driver 

More features				
Emergency 1-3 H	.33	DALI 1-10 V, switch DIM	.44	 Pag. 014

HANG 81.3 | 80 W | **230 V** | 10400 Lm | CRI > 90



TYPE	Cover	Finishing	Color
78103	Satin .1	White .11	2700 K .EW
	Opal .2	Anod. Alum .14	3000 K .WW
		Black .18	3500 K .LW
			4000 K .NW
			6500 K .CW
			Tunable CAS▲MBI .TW



Driver integrato
Integrated driver 


More features				
Emergency 1-3 H	.33	DALI 1-10 V, switch DIM	.44	 Pag. 014

HANG 81.4 | 40 W DOWN / 19,2 W UP | 230 V | 5200 Lm DOWN / 1920 Lm UP | CRI > 90 | IP40 | A++



TYPE

78104



each lenght from 400 mm to 1000 mm

Cover		Finishing		Color	
Satin	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
				3500 K	.LW
				4000 K	.NW
				6500 K	.CW
				Tunable	CASAMBI .TW

Driver integrato
Integrated driver 

More features


Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

HANG 81.5 | 60 W DOWN / 28,8 W UP | 230 V | 7800 Lm DOWN / 2880 Lm UP | CRI > 90 | IP40 | A++



TYPE

78105



each lenght from 1001 mm to 1500 mm

Cover		Finishing		Color	
Satin	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
				3500 K	.LW
				4000 K	.NW
				6500 K	.CW
				Tunable	CASAMBI .TW

Driver integrato
Integrated driver 

More features


Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

HANG 81.6 | 80 W DOWN / 38,4 W UP | 230 V | 10400 Lm DOWN / 3840 Lm UP | CRI > 90 | IP40 | A++



TYPE

78106



each lenght from 1501 mm to 2000 mm

Cover		Finishing		Color	
Satin	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
				3500 K	.LW
				4000 K	.NW
				6500 K	.CW
				Tunable	CASAMBI .TW

Driver integrato
Integrated driver 

More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

