




HANG 85.1 | 40 W | 230 V | 5200 Lm | CRI > 90

IP40      A++



TYPE	
78501	
	
each lenght from 400 mm to 1000 mm	

Cover	Finishing	Color
 .2	 .11	 .EW
 .3	 .18	 .WW
		 .LW
		 .NW
		 .CW
		 .TW
controlled by CAS  MBI		




Driver integrato
Integrated driver 





More features	
Emergency 1-3 H	.33
DALI 1-10 V, switch DIM	.44
	Pag. 014

HANG 85.2 | 60 W | 230 V | 7800 Lm | CRI > 90

IP40      A++



TYPE	
78502	
	
each lenght from 1001 mm to 1500 mm	

Cover	Finishing	Color
 .2	 .11	 .EW
 .3	 .18	 .WW
		 .LW
		 .NW
		 .CW
		 .TW
controlled by CAS  MBI		




Driver integrato
Integrated driver 





More features	
Emergency 1-3 H	.33
DALI 1-10 V, switch DIM	.44
	Pag. 014

HANG 85.3 | 80 W | 230 V | 10400 Lm | CRI > 90

IP40      A++



TYPE	
78503	
	
each lenght from 1501 mm to 2000 mm	

Cover	Finishing	Color
 .2	 .11	 .EW
 .3	 .18	 .WW
		 .LW
		 .NW
		 .CW
		 .TW
controlled by CAS  MBI		



Driver integrato
Integrated driver 

More features	
Emergency 1-3 H	.33
DALI 1-10 V, switch DIM	.44
	Pag. 014

HANG 85

FINISHING

---.11



CROMALINE

