

HANG 85

FINISHING

---.11



CROMALINE




CODE COMPOSITION: type + cover + finishing + color (+ more features) + xxxx mm


Tutti i parametri tecnici si riferiscono alla lampada nella sua lunghezza massima
All technical features refer to the lighting fixture in its maximum length

HANG 85.1 | 40 W | 230 V | 5200 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2		3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW




Driver integrato
Integrated driver

More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 85.2 | 60 W | 230 V | 7800 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2		3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW




Driver integrato
Integrated driver


More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014

HANG 85.3 | 80 W | 230 V | 10400 Lm | CRI > 90

IP40 A++



Cover	Finishing	Color
Transp .1	White .11	2700 K .EW
Opal .2		3000 K .WW
		3500 K .LW
		4000 K .NW
		6500 K .CW
		Tunable CASAMBI .TW



Driver integrato
Integrated driver

More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014


HANG 85.4 | 40 W DOWN / 19,2 W UP | 230 V | 5200 Lm DOWN / 1920 Lm UP | CRI > 90

IP40 A++



TYPE

78504



each length from 400 mm to 1000 mm

Cover

- Transp .1
- Opal .2

Finishing

- White .11

Color

- 2700 K .EW
- 3000 K .WW
- 3500 K .LW
- 4000 K .NW
- 6500 K .CW
- Tunable CASAMBI .TW

Driver integrato

Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014


HANG 85.5 | 60 W DOWN / 28,8 W UP | 230 V | 7800 Lm DOWN / 2880 Lm UP | CRI > 90

IP40 A++



TYPE

78505



each length from 1001 mm to 1500 mm

Cover

- Transp .1
- Opal .2

Finishing

- White .11

Color

- 2700 K .EW
- 3000 K .WW
- 3500 K .LW
- 4000 K .NW
- 6500 K .CW
- Tunable CASAMBI .TW

Driver integrato

Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014


HANG 85.6 | 80 W DOWN / 38,4 W UP | 230 V | 10400 Lm DOWN / 3840 Lm UP | CRI > 90

IP40 A++



TYPE

78506



each length from 1501 mm to 2000 mm

Cover

- Transp .1
- Opal .2

Finishing

- White .11

Color

- 2700 K .EW
- 3000 K .WW
- 3500 K .LW
- 4000 K .NW
- 6500 K .CW
- Tunable CASAMBI .TW

Driver integrato

Integrated driver



More features

Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 Pag. 014



ABBRUSCATO COSTRUZIONI
Milan