

50406.--.---.01

50406.--.---.02

FINISHING

---.14 ---.18




CODE COMPOSITION: type + cover + finishing + color (+ more features) + xxxx mm

Tutti i parametri tecnici si riferiscono alla lampada nella sua lunghezza massima
All technical features refer to the lighting fixture in its maximum length


ROD 1 | 14,4 W | 24 V | 1870 Lm | CRI > 90

IP65     A++



TYPE
50404

18
each lenght from 200 mm to 1000 mm

Cover	Finishing
 Transp .1	 Anod. Alum .14
 Opal .2	 Anod. Black .18

Application	Color
 Recessed .1	 2700 K .EW
 Ceiling .2	 3000 K .WW
	 3500 K .LW
	 4000 K .NW

Accessories




Kit fissaggio incluso
Fixing kit included

Driver remoto
Remote Driver






ROD 2 | 21,6 W | 24 V | 2805 Lm | CRI > 90

IP65     A++



TYPE
50405

18
each lenght from 1001 mm to 1500 mm

Cover	Finishing
 Transp .1	 Anod. Alum .14
 Opal .2	 Anod. Black .18

Application	Color
 Recessed .1	 2700 K .EW
 Ceiling .2	 3000 K .WW
	 3500 K .LW
	 4000 K .NW

Accessories




Kit fissaggio incluso
Fixing kit included

Driver remoto
Remote Driver






ROD 3 | 28,8 W | 24 V | 3740 Lm | CRI > 90

IP65     A++



TYPE
50406

18
each lenght from 1501 mm to 2000 mm

Cover	Finishing
 Transp .1	 Anod. Alum .14
 Opal .2	 Anod. Black .18

Application	Color
 Recessed .1	 2700 K .EW
 Ceiling .2	 3000 K .WW
	 3500 K .LW
	 4000 K .NW

Accessories



Kit fissaggio incluso
Fixing kit included

Driver remoto
Remote Driver

