



FINISHING

---.11

---.14

---.18

CROMALINE



1 COMPOSIZIONI QUADRANGOLARI QUADRANGULAR COMPOSITIONS

E' possibile ottenere composizioni quadrate o rettangolari bi-emissione. Scegliendo un MASTER e tre SLAVE (con misure identiche in caso di composizioni di forma quadrata o con due dimensioni differenti in caso di composizione rettangolare), con quattro moduli angolari, si possono ottenere facilmente composizioni bi-emissione con angoli a 90°. A richiesta il prodotto è realizzabile anche nella versione mono-emissione con luce diretta o indiretta. Il prodotto è disponibile sia con alimentatore remoto che con alimentatore incluso nel rosone a soffitto.

It is possible to obtain square or rectangular bi-emission compositions. By choosing a MASTER and three SLAVES (with identical measurements in the case of square-shaped compositions or with two different dimensions in the case of a rectangular composition), with four angular modules, bi-emission compositions can be obtained with 90° angles. On request, the product can also be produced in the mono-emission version with direct or indirect light. The product is available either with remote power supply or with power supply included in the ceiling rose.

CODE COMPOSITION: master + 3 slave

2 COMPOSIZIONI CUSTOM CUSTOM COMPOSITIONS

Si possono realizzare composizioni angolari di qualsiasi tipo scegliendo la forma e la dimensione preferite. Per ottenere la composizione che più si adatta all'ambiente da illuminare, è possibile - una volta scelta la lunghezza del MASTER - aggiungere un numero di moduli angolari e di barre SLAVE, a seconda delle vostre esigenze. A richiesta il prodotto è realizzabile anche nella versione mono-emissione con luce diretta o indiretta. Il prodotto è disponibile sia con alimentatore remoto che con alimentatore incluso nel rosone a soffitto. La composizione verrà fornita provvista di terminali di chiusura.

You can make any type of angular compositions by choosing the preferred shape and size. To obtain the composition that best suits the environment to be illuminated, it is possible - once chosen the length of the MASTER - to add a number of angular modules and SLAVE bars, depending on your needs. On request, the product can also be produced in the mono-emission version with direct or indirect light. The product is available either with remote power supply or with power supply included in the ceiling rose. The composition will be provided with closing terminals.


CODE COMPOSITION: master + X slave

MASTER SL-58.1 | 21,6 W DOWN / 9,6 W UP | 24 V | 3240 Lm DOWN / 960 Lm UP | CRI > 90



TYPE

85801



each lenght from 200 mm to 1000 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

Accessories

D.58.101

Rosone con driver integrato
Base for ceiling driver included



Driver remoto
Remote Driver



Pag. 454

More features


Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

MASTER SL-58.2 | 32,4 W DOWN / 14,4 W UP | 24 V | 4860 Lm DOWN / 1440 Lm UP | CRI > 90



TYPE

85802



each lenght from 1001 mm to 1500 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

Accessories

D.58.151

Rosone con driver integrato
Base for ceiling driver included



Driver remoto
Remote Driver



Pag. 454

More features


Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

MASTER SL-58.3 | 43,2 W DOWN / 19,2 W UP | 24 V | 6480 Lm DOWN / 1920 Lm UP | CRI > 90



TYPE

85803



each lenght from 1501 mm to 2000 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

Accessories

D.58.201

Rosone con driver integrato
Base for ceiling driver included



Driver remoto
Remote Driver



Pag. 454

More features


Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

SLAVE SL-58.1 | 21,6 W DOWN / 9,6 W UP | 24 V | 3240 Lm DOWN / 960 Lm UP | CRI > 90



TYPE

85804



each lenght from 200 mm to 1000 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

More features


CROMALINE Pag. 014

SLAVE SL-58.2 | 32,4 W DOWN / 14,4 W UP | 24 V | 4860 Lm DOWN / 1440 Lm UP | CRI > 90



TYPE

85805



each lenght from 1001 mm to 1500 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

More features


CROMALINE Pag. 014

SLAVE SL-58.3 | 43,2 W DOWN / 19,2 W UP | 24 V | 6480 Lm DOWN / 1920 Lm UP | CRI > 90



TYPE

85806



each lenght from 1501 mm to 2000 mm

Cover		Finishing		Color	
Transp	.1	White	.11	2700 K	.EW
Opal	.2	Anod. Alum	.14	3000 K	.WW
		Anod. Black	.18	3500 K	.LW
				4000 K	.NW

More features

CROMALINE Pag. 014