

TASK 81.1 | 40 W | 230 V | 3000 Lm | CRI > 90 | UGR ≤ 19

IP40  A++



TYPE
78111
40
80
each lenght from 400 mm to 1000 mm

Finishing	
White	.11
Anod. Alum	.14
Black	.18

Application	
Suspension	.1
Ceiling	.2
Recessed	.3

Color	
2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW



Driver integrato
Integrated driver

More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

TASK 81.2 | 60 W | 230 V | 4500 Lm | CRI > 90 | UGR ≤ 19

IP40  A++



TYPE
78112
40
80
each lenght from 1001 mm to 1500 mm

Finishing	
White	.11
Anod. Alum	.14
Black	.18

Application	
Suspension	.1
Ceiling	.2
Recessed	.3

Color	
2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW



Driver integrato
Integrated driver

More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

TASK 81.3 | 80 W | 230 V | 6000 Lm | CRI > 90 | UGR ≤ 19

IP40  A++



TYPE
78113
40
80
each lenght from 1501 mm to 2000 mm

Finishing	
White	.11
Anod. Alum	.14
Black	.18

Application	
Suspension	.1
Ceiling	.2
Recessed	.3

Color	
2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW



Driver integrato
Integrated driver

More features
Emergency 1-3 H .33 DALI 1-10 V, switch DIM .44 CROMALINE Pag. 014

78111.--.1

78111.--.2

FINISHING
---.11 ---.14 CROMALINE




78111.--.3

TASK 81B.1 | 40 W DOWN / 19,2 W UP | 230 V | 3000 Lm DOWN / 1920 Lm UP | CRI > 90 | UGR ≤ 19 | IP40



TYPE
78114



Finishing

White	.11
Anod. Alum	.14
Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW

Driver integrato
Integrated driver


More features

Emergency 1-3 H	.33	DALI 1-10 V, switch DIM	.44	CROMALINE	Pag. 014
-----------------	-----	-------------------------	-----	-----------	----------

TASK 81B.2 | 60 W DOWN / 28,8 W UP | 230 V | 4500 Lm DOWN / 2880 Lm UP | CRI > 90 | UGR ≤ 19 | IP40



TYPE
78115



Finishing

White	.11
Anod. Alum	.14
Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW

Driver integrato
Integrated driver


More features

Emergency 1-3 H	.33	DALI 1-10 V, switch DIM	.44	CROMALINE	Pag. 014
-----------------	-----	-------------------------	-----	-----------	----------

TASK 81B.3 | 80 W DOWN / 38,4 W UP | 230 V | 6000 Lm DOWN / 3840 Lm UP | CRI > 90 | UGR ≤ 19 | IP40



TYPE
78116



Finishing

White	.11
Anod. Alum	.14
Black	.18

Color

2700 K	.EW
3000 K	.WW
3500 K	.LW
4000 K	.NW
6500 K	.CW
Tunable	CASAMBI .TW

Driver integrato
Integrated driver

More features

Emergency 1-3 H	.33	DALI 1-10 V, switch DIM	.44	CROMALINE	Pag. 014
-----------------	-----	-------------------------	-----	-----------	----------

FINISHING

---.11

---.14

CROMALINE

